


SKF FY 1.1/4 WF bearing units

Bearing No. FY 1.1/4 WF



FY 1.1/4 WF Bearing 2D drawings and 3D CAD models

Bore Diameter	31.75 mm
d	31.75 mm
s1	32,3 mm
A1	34,5 mm
B1	51,1 mm
G	12 mm
J	92 mm
L	118 mm
T	53,3 mm
A2	13 mm
Weight	1,6 Kg
Basic dynamic load rating (C)	25,5 kN
Basic static load rating (C0)	15,3 kN
Fatigue load limit (Pu)	0,655
Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.632
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Eccentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion



NTN DRIVESHAFT ANDERLU, INC.

Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	YEL 207-104-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	4 Bolt Square Flange Block; 1-1/4" Bore; 5.1" Bolt Circle; 3-5/8" Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 2-1/64" Length Thru Bore; Relubricat
Other Features	Single Row Standard Duty Wide Inner Race Open End Has Flinger Y Bearing
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	FY 1.1/4 WF
Weight / LBS	3.6
Length Thru Bore	2.016 Inch 51.2 Millimeter
Bore	1.25 Inch 31.75 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Bolt Spacing	3.625 Inch 92.08 Millimeter
Nominal Bolt Circle Diameter Round	5.1 Inch 130 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Housing material	Cast iron



NTN DRIVESHAFT ANDERIU, INC.

D_a	106.4 mm
D_{b1}	87 mm
D_{b2}	95 mm
A	34.5 mm
A_1	13 mm
A_3	3.2 mm
A_5	24.5 mm
B_1	51.1 mm
N	14 mm
s_1	32.3 mm
R_G	1/4-28 UNF
R_1	22.5 mm
D_N	6.5 mm
SW_N	7 mm
G_N	1/4-28 SAE-LT
J_6	106 mm
J_7	29 mm
N_4	4 mm
Basic dynamic load rating C	25.5 kN
Basic static load rating C_0	15.3 kN
Fatigue load limit P_u	0.655 kN
Limiting speed	5300 r/min
Mass bearing unit	1.45 kg
Thread grub screw G_2	3/8-24 UNF
Hexagonal key size for grub screw N	4.763 mm
Recommended tightening torque for grub screw	16.5 N · m
Recommended diameter for attachment bolts, mm G	12 mm
Recommended diameter for attachment bolts, inch G	0.5 in