



160 mm x 340 mm x 68 mm NSK NUP332EM cylindrical roller bearings

Bearing No. NUP332EM

NUP332EM Bearing 2D drawings and 3D CAD models

Size	160x340x68 mm
Bore Diameter	160 mm
Outer Diameter	340 mm
Width	68 mm
d	160 mm
Fw	204 mm
D	340 mm
B	68 mm
C	68 mm
r min.	4 mm
r1 min.	4 mm
da min.	176 mm
Da max.	324 mm
db max.	199 mm
db min	176 mm
ra max.	3 mm
rb max.	3 mm
S	3,2 mm
Db max	324 mm
Weight	32,1 Kg
Basic dynamic load rating (C)	860 kN
Basic static load rating (C0)	1050 kN
(Grease) Lubrication Speed	1700 r/min
hidYobi	NUP332EM
LangID	1



NTN DRIVESHAFT ANDERIU, INC.

D_	340
Macha rpm	3600
B_	68
hidTable	ecat_NSCLDR
Oil rpm	2000
rb	3
mass	32.5
GRS rpm	1700
ra	3
db max	199
TSR rpm	1900
C0	1050
DE_	300
Prod_Type3	CRB_SR_NUP
da	176
DA_	48
Z_	14
D_a max	324
yobi	NUP332EM
dd min	228
C_conv	860000
ALPHA_	0
SDM_	252
r	4
dc min	211
KBRG	4165
SBRG	3
r1	4
DI_	204